

AutomationDirect » C-more

V6.0 HUNDREDS OF IMPROVEMENTS



ALLEN BRADLEY® PLC DRIVER SUPPORT



REMOTE ACCESS AND CONTROL TOUCH YOUR PANEL FROM ANYWHERE



AutomationDirect » C-more HMI - Color TFT - IP65 NEMA 4/4X

Hardware Features

- 800MHz CPU, 64K Colors, LED Back-lights, 26MB to 82MB project memory depending on model
- 12 to 24 VDC powered (optional EA-AC power supply available)
- Built-in Real-Time Clock with 30 day backup (No battery required)



Part Number	Size	Resolution	Brightness Nits	Serial Ports	Ethernet	USB Ports A & B	Memory Slot	Audio Out	HDMI Out
EA9-T6CL-R	6"	320 x 240 QVGA	280	1		2	1		
EA9-T6CL	6"	320 x 240 QVGA	280	3	1	2	1	1	
EA9-T7CL-R	7" Wide	800 x 480 WVGA	350	1	1	2	1		
EA9-T7CL	7" Wide	800 x 480 WVGA	350	3	1	2	1	1	
EA9-T8CL	8"	800 x 600 SVGA	310	3	1	2	1	1	
EA9-T10WCL	10" Wide	1024 x 600 WSVGA	240	3	1	2	1		
EA9-T10CL	10"	800 x 600 SVGA	280	3	1	2	1	1	
EA9-T12CL	12"	800 x 600 SVGA	280	3	1	2	2	1	1
EA9-T15CL-R	15"	1024 x 768 XGA	280	1	1	2	2		
EA9-T15CL	15"	1024 x 768 XGA	280	3	1	2	2	1	1

Software Features

- >50 Objects including 16 pen trends, switches, PID trend faceplate, PID bar graphs
- Event Manager allows for Logging and Notifications
- Language Support for objects in German, French, Italian, Spanish, Chinese and Japanese Characters
- Project simulator, Bitmap animation, E-mail messaging, Built-in FTP server / Web server, Pop-up windows
- Up to 9999 screens depending on complexity, Built-in soft keypad for numeric and alphanumeric entry
- Password protection for every touch object, Passwords for up to eight user groups
- Unlimited levels of undo and 16 levels of redo, 40-character tag names, overlapping objects, background screens
- Data logging to USB/SD Flash Drive
- Historical alarms with time and date stamp along with alarm frequency reporting
- Supports simultaneous communication to multiple brands of PLCs/PACs



Remote HMI

- PC Web Browser, Use your Mobile Device - C-more Remote HMI App - download from iTunes App Store, Google Play and Amazon
- No Additional Hardware required - feature resides in C-more panel - configure the network settings in the panel project - connect network
- Multilevel Logon Security - 3 remote access user accounts can be configured and stored in the panel - up to 5 remote users simultaneously
- View only, View and allow Screen Change only, Full Control
- Program Notification Tags to activate alarms, events or notifications to alert local operators that a remote user is connected

Supported Drivers

- Modbus RTU, Modbus TCP/IP, A-B Ethernet/IP Server Generic IO Messaging, A-B Ethernet/IP Client, A-B DF1 & DH485
- GE, Omron, Mitsubishi, and Siemens Serial and Ethernet
- All AutomationDirect PLCs - all Serial and Ethernet Communications