

Automation Direct - C-more HMI - Color TFT - Indoor Rated - IP65  
NEMA 4/4X (0-50 deg C) - (UL508 E157382)  
Programming Software - EA9-PGMSW  
12 to 24 VDC (18Watts at 24Vdc) powered (optional EA-AC power supply available)  
2 year warranty with 30 day money back policy

Part Number	Size	Resolution - Color TFT All	Brightness Nits	Serial Ports	Ethernet	USB Ports A & B	Memory Slot	Audio Out	Memory
EA9-T6CL-R	6"	320 x 240 QVGA	280	1		2	1		26MB
EA9-T6CL	6"	320 x 240 QVGA	280	3	1	2	1	1	26MB
EA9-T7CL-R	7" Wide	800 x 480 WVGA	350	1	1	2	1		26MB
EA9-T7CL	7" Wide	800 x 480 WVGA	350	3	1	2	1	1	26MB
EA9-T8CL	8"	800 x 600 SVGA	310	3	1	2	1	1	26MB
EA9-T10WCL	10" Wide	1024 x 600 WSVGA	240	3	1	2	1		26MB
EA9-T10CL	10"	800 x 600 SVGA	280	3	1	2	1	1	26MB
EA9-T12CL	12"	800 x 600 SVGA	280	3	1	2	1	1	82MB
EA9-T15CL-R	15"	1024 x 768 XGA	280	1	1	2	2		82MB
EA9-T15CL	15"	1024 x 768 XGA	280	3	1	2	2	1	82MB

Idc High Performance Touchscreen HMI - Color TFT - IP67F - NEMA 4X  
Outdoor Rated (-20 to 60 deg C) C1 D2, DNV, ABS - Scripting -  
Multimedia (UL61010-2-201)  
Programming Software - SW1A-W1C  
24Vdc - 25W maximum  
3 year warranty

HG2G-V5FT22TF-B	5.7"	640 x 480 VGA	800	2	1	2	1		56MB
HG3G-V8XT22MF-B	8.4"	1024 x 768 XVGA	800	2	1	2	1	1 + Video In	56MB
HG3G-VAXT22MF-B	10.4"	1024 x 768 XVGA	700	2	1	2	1	1 + Video In	56MB
HG4G-VCXT22MF-B	12.1"	1024 x 768 XVGA	600	2	1	2	1	1 + Video In	56MB
HG5G-VFXT22MF-B	15.4"	1024 x 768 XVGA	650	2	1	2	1	1 + Video In	56MB

Proface SP5000X Series HMI - Color TFT - IP66F - NEMA 4X Outdoor  
Rated - Sunlight Readable, Anti-Glare Surface, UV Resistive, C1 D2  
(UL61010-2-201)  
Temp Ratings - 7" (-20 to 60 deg C) - 12" (-30 to 70 Deg C) - 15" (-30 to 65 deg C)  
Extreme has additional Corrosive Environment Protection  
Programming Software - GP-Pro EX  
12 / 24 Vdc - up to 68Watt maximum  
2 year warranty

PFXSP5490WAD + PFXSP5B90 + PFXZCHBMFBL1	7"	800 x 480 WVGA	1000	2	2	3	2	1	1GB
PDXSP5490WADF0H + PFXSP5B90F0H + PFXZCHBMFBL1	7"	800 x 480 WVGA Extreme	1000	2	2	3	2	1	1GB
PFXSP5690WAD + PFXSP5B90 + PFXZCHBMFBL1	12"	1280 x 800 WXGA	1000	2	2	3	2	1	1GB
PFXSP5690WADF0H + PFXSP5B90F0H + PFXZCHBMFBL1	12"	1280 x 800 WXGA - Extreme	1000	2	2	3	2	1	1GB
PFXSP5790WAD + PFXSP5B90 + PFXZCHBMFBL1	15"	1366 x 768 FWXGA	1000	2	2	3	2	1	1GB
PFXSP5790WADF0H + PFXSP5B90F0H + PFXZCHBMFBL1	15"	1366 x 768 FWXGA Extreme	1000	2	2	3	2	1	1GB

