

Part Number	Size	Power (Voltage)	Op Temp Deg C Fanless	Resolution Color TFT Touch IP66 Front	Brightness (Nits)	CPU, RAM, SSD, OS	Ports	Agency	Approvals Special
<b>Advantech</b>									
TPC-1282T	12.1"	24Vdc	(0 to 50)	1024 x 768 Multi	600	Intel Core i3, 4GB, 256GB, Win 7, 10 Pro/Emb	(2)RJ45GB,(2)Serial,(2)USB,Audio IO	<b>UL 60950-1</b>	
TPC-1581WP	15.6"	24Vdc	(0 to 55)	1366 x 768 Capac	300	Intel Core i3, 4GB, 256GB, Win 7, 10 Pro/Emb	(2)RJ45GB,(2)Serial,(2)USB,Audio IO	<b>UL 60950-1</b>	
TPC-1881WP	18.5"	24Vdc	(0 to 55)	1366 x 768 Capac	300	Intel Core i3, 4GB, 256GB, Win 7, 10 Pro/Emb	(2)RJ45GB,(2)Serial,(2)USB,Audio IO	<b>UL 60950-1</b>	
TPC-1881WPH	18.5"	24Vdc	(0 to 55)	1366 x 768 Capac	300	Intel Core i3, 4GB, 256GB, Win 7, 10 Pro/Emb	(2)RJ45GB,(2)Serial,(2)USB,Audio IO	<b>UL 60950-1</b>	C1D2
<b>Pro-face</b>									
PS-5600W	12.1"	12/24Vdc, 100-240VAC	(0 to 55)	1280 x 800 Multi	400	Intel Core i7, 16GB, 240GB, Win10 ioT64	(2)RJ45GB,(1)Serial,(4)USB,(2)PCIe	CSA/UL61010	C1D2, ATEX, DNV
PS-5700W	15.6"	12/24Vdc, 100-240VAC	(0 to 55)	1366 x 768 Multi	400	Intel Core i7, 16GB, 240GB, Win10 ioT64	(2)RJ45GB,(1)Serial,(4)USB,(2)PCIe	CSA/UL61010	C1D2, ATEX, DNV
PS-5800W	18.5"	12/24Vdc, 100-240VAC	(0 to 55)	1366 x 768 Multi	300	Intel Core i7, 16GB, 240GB, Win10 ioT64	(2)RJ45GB,(1)Serial,(4)USB,(2)PCIe	CSA/UL60950	
PS-5900W	21.5"	12/24Vdc, 100-240VAC	(0 to 55)	1920 x 1080 Multi	300	Intel Core i7, 16GB, 240GB, Win10 ioT64	(2)RJ45GB,(1)Serial,(4)USB,(2)PCIe	CSA/UL60950	
<b>Moxa</b>									
MPC-2070	7"	12/24Vdc	(-40 to 70)	800 x 480	350 or 1000	Atom, 8GB, 128GB, Win7,10 Pro/Emb	(2)RJ45GB,(2)Serial,(2)USB	<b>UL 60950-1</b>	C1D2, ATEX, DNV
MPC-2101	10"	24/48Vdc	(-40 to 70)	1024 x 768	500 or 1000	Atom, 8GB, 128GB, Win7,10 Pro/Emb	(2)M12GB,(2)Serial,(1)M12 USB	<b>UL 62368-1</b>	EN 50155 (Rail)
MPC-2120	12"	12/24Vdc	(-40 to 70)	1024 x 768	500 or 1000	Atom, 8GB, 128GB, Win7,10 Pro/Emb	(2)RJ45GB,(2)Serial,(2)USB	<b>UL 60950-1</b>	C1D2, ATEX, DNV
MPC-2121	12"	24/48Vdc	(-40 to 70)	1024 x 768	500 or 1000	Atom, 8GB, 128GB, Win7,10 Pro/Emb	(2)M12GB,(2)Serial,(1)M12 USB	<b>UL 62368-1</b>	EN 50155 (Rail)
MPC-2150	15"	12/24Vdc, 100-240VAC	(-40 to 70)	1024 x 768	1000	Intel Core i7, 8GB, Win7,10 Pro/Emb	(2)RJ45GB,(2)Serial,(4)USB	<b>UL 60950-1</b>	C1D2, ATEX, DNV
EXPC-1519	19"	12/24Vdc, 100-240VAC	(-40 to 70)	1280 x 1024	1000	Intel Core i7, 4GB, Win7,10 Pro/Emb	(2)RJ45,(2)FiberST,(2)Serial,(4)USB	<b>UL 60950-1</b>	C1D2, ATEX, DNV
MPC-2190	19"	12/24Vdc, 100-240VAC	(-15 to 55)	1280 x 1024	300	Intel Core i7, 8GB, Win7,10 Pro/Emb	(2)RJ45GB,(2)Serial,(4)USB	<b>UL 60950-1</b>	ABS, CCS, DNV
MPC-2240	24"	12/24Vdc, 100-240VAC	(-15 to 55)	1920 x 1080	300	Intel Core i7, 8GB, Win7,10 Pro/Emb	(2)RJ45GB,(2)Serial,(4)USB	<b>UL 60950-1</b>	ABS, CCS, DNV
MPC-2260	26"	12/24Vdc, 100-240VAC	(-15 to 55)	1920 x 1200	300	Intel Core i7, 8GB, Win7,10 Pro/Emb	(2)RJ45GB,(2)Serial,(4)USB	<b>UL 60950-1</b>	ABS, CCS, DNV



**ADVANTECH**



**Pro-face**  
by Schneider Electric



**MOXA**